



# STRONG COVER

## Datasheet

Quality Covers strong cover is an ideal covering material for universal protection against contamination and damage to the surface. It is used indoors.

### Material composition

Top side: 100% recycled PET fibers

Underside: waterproof LDPE coating with anti-slip

### Specifications

Weight	170gr/m <sup>2</sup>
Dimensions	1x45m 1x50m
Packaging	Packed in bag on euro pallets.
Color	White
Usability	Application properties are not time-dependent (up to 40° C)
Storage	Dry and protected from moisture, preferably in original packaging

### Area of application

Quality Covers strong cover protects indoor floors. The use of white light premium prevents damage and contamination to the surface.

### Properties

- Very strong
- Liquid tight
- Lightweight
- Anti-slip coating on the underside
- Scrappable
- Fine dust filtered



# STRONG COVER

## Datasheet

### Processing

- Make the substrate dry, clean and dust-free
- Switch off underfloor heating
- Lay the strong cover flat on the substrate
- Overlap by 10 cm and seal the material with an appropriate tape
- Always test if the product is suitable for the subfloor

### Notes

Quality Covers strong cover is not suitable for newly laid floors that still need to breathe or harden, in which case we recommend Quality Covers Breathable liner.

Strong cover is not resistant to aggressive substances, the substrate must be permanently dry, clean, free of dust and solvents.

### Certifications



*Our application recommendations are to support the buyer or processor and are based on our testing and experience. You are responsible for checking the suitability for the intended purpose, for example by testing on a small area. The manufacturer assumes no liability for any damage that may occur. No rights can be derived from this data sheet. Kwabo Techniek B.V. reserves the right to make technical changes and developments.*